

ABSTRACT

A vehicle jack of the type known as "Y" jacks having a vehicle support arm (2) and a support leg (1) on which the vehicle support arm pivots. The free end of the vehicle support arm (2) includes a vehicle support plate that receives an edge of the bodywork of the vehicle, and the support leg has a swivel mounted support foot that rotates on an axis essentially parallel to the movement axis of the vehicle support arm. A bar (23) is fixed to the beginning of the vehicle support arm (2) and passes through the interior of the support leg (1) until it enters between the base of the end of the said support leg (1) and the bottom of the foot (3), making contact with the foot.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.